

Valcon Filter Driers

- Economical System Protection for Residential Air Conditioning
- Manufactured and Stocked in North America
- ODF - Solid Copper Connections for Easy Installation
- Solid Core Construction with 40 Micron Filtration
- Maximum Working Pressure = 680 psig
- For use with CFC, HCFC and HFC refrigerants



Liquid Line Service

PCN	Model	R-410A Flow Capacity Tons @ 1psi ΔP
*060406	PF 032MF	2.8
*060410	PF 052	2.8
059689	TD 032	2.1
059690	TD 032S	2.5
059693	TD 052	2.2
059694	TD 052S	3.1
059695	TD 053	4.0
059696	TD 053S	4.9
059697	TD 082S	2.2
059698	TD 083	4.6
059699	TD 083S	4.7
059700	TD 084	7.3
059701	TD 084S	7.6
059704	TD 163	4.8
059935	TD 163S	5.3
059706	TD 164S	9.3
059708	TD 165S	14.2
059709	TD 303S	5.3
059710	TD 304	9.3
059713	TD 305S	15.7

Bi-Flow Service

PCN	Model	R-410A Flow Capacity Tons @ 1psi ΔP
059904	TBF 083S	5.1
059908	TBF 163S	5.2
059910	TBF 164S	8.1
059912	TBF 165S	8.7

Suction Line Service

PCN	Model	R-410A Flow Capacity Tons @ 2psi ΔP ¹
059898	TS 084S	1.8
060552	TS 085S	3.1
063442	TS 086S	3.8
059965	TS 164S	1.9
059887	TS 165S	2.9
059966	TS 166S	3.6
059888	TS 167S	3.9
059891	TS 306S	4.3
059892	TS 307S	5.3

* Filter only. Does not contain desiccant.

¹ Suction capacities are based on 20°F evaporating temperature.

