WM-2500SSWWC

Professional Solutions for Wine Cellar Climate Control



## **Key Features**

- Stable temperature between 50~65 °F for a properly insulated room in a normal environment
- Maintain humidity of 50~75% RH even when the environment becomes dry or humid
- The condensing units can be placed up to 75 ft away from the wine room, which will allow for extremely quiet operation
- These units require professional installation by a licensed refrigeration technician
- Perfect for storing cigars, chocolate, salami, and fine leather and furs (additional cost and customization required)

## **Specifications**

Cellar Size:	250 cu ft
Btu/h, CFM:	2500 Btu/h, 175 CFM
Decibel Rating:	53 dBA
Dimensions:	Evaporator: 16"W x 5-1/2"D x 36"H Condenser: 24"W x 18"D x 18"H
Electrical:	Evaporator: 115V/60Hz/1A Condenser: 115V/60Hz/5A
Weight:	Evaporator: 30 lbs Condenser: 40 lbs
Refrigerant:	R134a
Thermostat:	Advanced Digital Control Display

## Wine-Mate 2500SSWWC Split WallRecessed Wine Cooling System

## **Features**

Wine-Mate wall split cooling systems WM-2500~4500SSWWC are designed and used to provide a cold temperature between 50~65 °F for a properly insulated wine cellar. The wine cellar will maintain humidity range within 50~75% RH. These temperature and humidity ranges like in natural caves are optimized for long term storage of wine. SSWWC units consist of a condensing unit and an evaporator unit; they are connected by a liquid line and an insulated suction line. SSWWC condensing units can be located away from the wine cellars 75 ft so that noise and compressor vibration are isolated. SSWWC evaporator units can be installed inside a wine rack or between two wall studs, making them an ideal choice for wine cabinets or small wine rooms.