

Sleek and contemporary describe the Eutited collection of outdoor fixtures. It's minimalistic inspired, duel rectangular design shows that less is indeed sometimes more, finishes include Silver or Black. All fixtures include the latest in long life LED energy saving technology.

e.

and and the

Luttrell



F

566CHXL-BK-LED

(1) 27W LED

2295

1064

2700K

>90

14.25"

11.75″

29.5″

4.5" square

68"

36"

48"



| | Product | Source/ Wattage | Source Lumens | Delivered Lumens | ССТ | CRI | L/Ext. | w | н | Over- all H | Chain | Wire | Ceiling/Wall Plate |
|---|----------------------|--------------------|------------------|---------------------|-------|-----|--------|--------|--------|----------------|-------|------|--------------------|
| G | 566PHXLR-BK-LED | (1) 27W LED | 2295 | 1120 | 2700K | >90 | 14.25″ | 11.75″ | 30.5″ | | | | |
| н | 566PHBR-BK-LED | (1) 12W LED | 1094 | 512 | 2700K | >90 | | 10.5″ | 21.75″ | | | | |
| I | 566PHXLS-BK-LED | (1) 27W LED | 2295 | 1110 | 2700K | >90 | 14.25" | 11.75″ | 29" | | | | |
| J | 566PHBS-BK-LED | (1) 12W LED | 1094 | 504 | 2700K | >90 | | 10.5″ | 21.75″ | | | | |
| К | 566PHBR-567P-BK-LED | (1) 12W LED | 1094 | 512 | 2700K | >90 | | 10.5″ | 96.5″ | | | | |
| L | 566PHXLS-536P-BK-LED | (1) 27W LED | 2295 | 1110 | 2700K | >90 | 14.25″ | 11.75″ | 123″ | | | | |

Finish



| | Product | Source/ Wattage | Source Lumens | Delivered Lumens | ССТ | CRI | L/Ext. | W | н | Over- all H | Chain | Wire | Ceiling/Wall Plate |
|---|---------------------|--------------------|------------------|---------------------|-------|-----|--------|-------|--------|----------------|-------|------|--------------------|
| М | 566B-SL-LED | (1) 12W LED | 1094 | 448 | 2700K | >90 | 8.75″ | 8.75″ | 18" | | | | 4.75"W x 8"H |
| Ν | 566M-SL-LED | (1) 10W LED | 904 | 369 | 2700K | >90 | 7.5″ | 7.25″ | 15″ | | | | 4.75″W x 8″H |
| 0 | 566S-SL-LED | (1) 8W LED | 705 | 250 | 2700K | >90 | 5.75″ | 5.5″ | 11.75″ | | | | 4.5"W x 6.5"H |
| Ρ | 566PHBR-SL-LED | (1) 12W LED | 1094 | 512 | 2700K | >90 | | 10.5″ | 21.75″ | | | | |
| Q | 566PHBS-SL-LED | (1) 12W LED | 1094 | 504 | 2700K | >90 | | 10.5″ | 21.75″ | | | | |
| R | 566CHB-SL-LED | (1) 12W LED | 1094 | 520 | 2700K | >90 | | 10.5″ | 18" | 54″ | 36" | 48″ | 4.5" square |
| S | 566PHBR-567P-BA-LED | (1) 12W LED | 1094 | 512 | 2700K | >90 | | 10.5″ | 96.5″ | | | | |