

ASSEMBLY AND INSTALLATION INSTRUCTION

WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!

NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.

Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Hold Mounting Plate up against Outlet Box, while the Mounting Plate is leveled horizontally, use a pencil to mark the mounting holes, then drilling four holes in the wall and loaded plastic anchors. Attach the Mounting Plate to the wall, aligning the Plastic Anchors and Outlet Box mounting holes, lock it securely with the four Wood Screws and two Outlet Box Screws.
3. Guide the Black/White Supply Wires and Supply Ground Wire from Outlet Box through the center hole on the Mounting Plate.
 - 3.1 Using a Wire Nut, connect the White Fixture Wire to the White Supply Wire, connect the Black Fixture Wire to the Black Supply Wire, connect Fixture Ground Wire to Supply Ground Wire, or attach Fixture Ground Wire to the Mounting Plate with a green ground screw. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug. After the wires connected, tuck them into Outlet Box.
 - 3.2 Raise Back Plate against Mounting Plate and tighten with Mounting Screws.
4. **◆ IF YOU NEED FIXTURE ELECTRIC CORD ASSEMBLY TO THE FIXTURE LAMP, PLEASE PAUSE AND TAKE OUT FIXTURE WIRES NUTS OF THE BACK PLATE, THEN FOLLOW WIRING INSTRUCTIONS CAREFULLY.**
 - 4.1 **◆**This fixture includes 3pcs Pipes to be connected into various height. Measure and determine correct number of Pipes required. Slide the need Pipes to Fixture Electric Cord, connect all the Pipes together until secure.
 - 4.2 **◆**Using a Wire Nut, connect the White Fixture Wire to the Fixture Electric Cord ribbed wire, connect the Black Fixture Wire to the Fixture Electric Cord smooth wire, connect Fixture Ground Wire to the Mounting Plate with a green ground screw. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug.
 - 4.3 **◆**Raise Back Plate against Mounting Plate and tighten with Mounting Screws.
 - 4.4 **◆**Please appropriate location drilling two holes on the Pipe side, then loaded Plastic Anchors, raise the Clip onto the Pipe and tighten with Wood Screw.
5. Loosen the Adjuster, holding the arm adjust to appropriate location and locked.
6. Install the light bulbs(Not included) in accordance with the fixture's specifications.

NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
7. Your installation is now complete. Return the power to the Outlet Box and test the fixture.

