

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

Installation Steps:

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Outlet Box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Take this cross bar to outlet box with outlet box screws, tighten screws securely with screwdriver. The side of the mounting plate marked "GND" must face to out.
4. This lamp body includes 6pcs pipes to be connected into various height. Measure and determine correct number of pipes required. Feed the wires from lamp body through pipes and universal joint, connect the pipe to the thread nipple from lamp body. Thread the thread nipple to inside of each pipes, connect all the pipes and universal joint together until secure. Raise the canopy onto the end of universal joint, lock it securely with the spring shim and wing nut.
5. Take this lamp body assembly to ceiling outlet box, connect the electrical wires.
6. **NOTE: make wires connections:**

****Attach fixture ground wire to supply ground wire using a wire nut or attach them to the cross bar with a green ground screw.**

****Attach fixture white wire from lamp body to supply white wire or ridge wire from power source with a wire nut.**

****Attach fixture black wire from lamp body to supply black wire or smooth wire from power source with a wire nut.**

****Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.**

7. Make sure all wire connectors are secured and do not easily pull off with the slight tug. After wires are connected, tuck them carefully inside the Outlet Box.
8. Raise the canopy on to the outlet box, aligning thread nipple on cross bar with mounting hole in canopy and lock it securely with the column nut.
9. Raise the shade onto the lamp holder, lock it with the check ring until tight.
10. Install the light bulbs(Not included) in accordance with the fixture's specifications.

NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!

11. Your installation is now complete. Return power to the outlet box and test the lamp body.

