

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER!

NOTE: BEFORE INSTALLING, CONSULT LOCAL ELECTRICAL CODES FOR WIRING AND GROUNDING REQUIREMENT.

Installation Steps:

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Outlet Box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Assemble the Threaded Nipple onto the Cross Bar and lock it in place with a hex nut. Secure the Universal Joint onto the other end of Threaded Nipple.
4. This lamp body includes 6pcs Pipes to be connected into various heights. Measure and determine correct number of Pipes required. Feed the wires and Safety Cable from Lamp Holder through Pipe, Frame, Pipes, Collar Ring, Canopy and Universal Joint, connect the Pipe to the thread nipple from Lamp Holder. Thread the thread nipple to inside of each Pipes, connect all the Pipes and Universal Joint together until secure. Feed the Safety Cable through the small holes in the side of Column Nut, lock it securely with the screws.
5. Take this lamp body assembly to ceiling, attach the Cross Bar assembly to Outlet Box by using two Outlet Box Screws upwards, then connect the electrical wires.
6. **NOTE: make wires connections:**
 - **Attach fixture ground wire to supply ground wire using a wire nut or attach them to the mounting plate with a green ground screw.
 - **Attach fixture white wire from lamp body to supply white wire or ridge wire from power source with a wire nut.
 - **Attach fixture black wire from lamp body to supply black wire or smooth wire from power source with a wire nut.
 - **Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.
7. Make sure all wire connectors are secured and do not easily pull off with the slight tug. After wires are connected, tuck them carefully inside the Outlet Box. Raise the Canopy on to the Outlet Box, lock it securely with the Collar Ring.
8. Install the light bulbs (Not included) in accordance with the fixture's specifications.
NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
9. Raise the Glass Sheet to Frame side and use Handle Screw to secure Glass Sheet as well as Plastic Shim onto Frame. **Note: handle screws do not lock too tightly!!**
10. Your installation is now complete. Return power to the outlet box and test the lamp body.

