

## ASSEMBLY AND INSTALLATION (Continued)

### FLUSH MOUNT FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

## CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### ASSEMBLY AND INSTALLATION

1. Thread the FIXTURE SCREWS (4) half way into the back of the MOUNTING BRACKET (2). Thread the HEX NUTS (11) onto the FIXTURE SCREWS (4) until they are next to the MOUNTING BRACKET (2). Do not tighten the HEX NUTS (11). Check the pan mounting holes against the position of the FIXTURE SCREWS (4) for proper alignment and spacing.
2. Pull the SUPPLY WIRES (5 & 6) and the HOUSE GROUND WIRE (7) out from the OUTLET BOX (1) and attach the MOUNTING BRACKET (2) to the OUTLET BOX (1) using the slotted holes on the MOUNTING BRACKET (2) and the MOUNTING SCREWS (3) provided.
3. Make the wiring connections: Connect the FIXTURE GROUND WIRE (10) to the HOUSE GROUND WIRE (7) using a WIRE CONNECTOR (12)(no included). As shown. Connect the WHITE SUPPLY WIRE (5) to the WHITE ( or BIBBED ) FIXTURE WIRE (8), connect the BLACK SUPPLY WIRE (6) to the BLACK ( or SMOOTH ) FIXTURE WIRE (9) using WIRE CONNECTOR (12).

4. Carefully tuck all wiring back into the OUTLET BOX (1). Locate the FIXTURE PAN (13) over the OUTLET BOX (1), positioning the FIXTURE SCREWS (4) through the pan mounting holes. The length of the FIXTURE SCREWS (4) can be adjusted by removing the PAN (13) from over the OUTLET BOX (1) and screwing the FIXTURE SCREWS (4) in or out of the MOUNTING BRACKET (2) to the proper position and lock in position by tightening the HEX NUTS (11) against the MOUNTING BRACKET (2). Place the PAN (13) back over the OUTLET BOX (1) and position the FIXTURE SCREWS (4) back through the pan mounting holes and secure in place by screwing and tightening the THUMB NUTS (20).
5. Install light bulb(s) at the lamp type and wattage specified on the fixture. Thread the HEX NUT (15) onto the CENTER PIPE (16), and the CENTER PIPE (16) into the COUPLING (14), Secure the GLASS SHADE (17) and the CAP (18) with the FINIAL KNOB (19).

INSTALLATION IS NOW COMPLETED

