

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
www.zoeller.com

COMPARE THESE FEATURES:

- Use fully or partially submerged
- Durable polypropylene housing
- 3-prong power cord, 9 ft. or 20 ft.
- 115 Volt/Single Phase/60 Hz
- High quality sealed motor
- Thermal-overload protected motor
- Model 42 is adaptable for use with standard garden hose (fitting included), 1" NPT pipe, or 1¼" slip fit (use discharge hose kit P/N 1010-0117)
- Model 44 is adaptable for use with standard garden hose (fitting included), 1-1/4" Female NPT or 3/4" female NPT adapter
- Model LM44 with Automatic Operation. Utility applications only*
- Model 46 is 2" NPT discharge with 2" hose adapter
- Screened bottom may be removed to allow easy cleaning
- Use indoors or outdoors
- Typical applications: dewatering and filling
- Oil free (Models 42 and 44 only)
- Models 42 and 44 remove water from any flat surface down to 1/8"; model 46 will pump down to 1"
- Lightweight and Portable
- Compact design: Models 42 and 44 will fit in a 7" opening; model 46 will fit in an 8" opening
- One-year limited warranty
- Temperature rating 104°F (40°C)
- Nonautomatic - 42, 44 and 46 models

Model	HP	Amps	Max Width	Max Height	Weight
42	1/6	1.5	6	9-1/2	7.3 lbs.
44	1/4	2.5	6	11-3/4	7.7 lbs.
LM44	1/4	2.5	6	11-3/4	8.7 lbs.
46	1/2	6.0	8	14-1/2	16 lbs.

TOTAL DYNAMIC HEAD FLOW PER HOUR

MODEL		42		44		46	
Feet	Meters	Gal.	Liters	Gal.	Liters	Gal.	Liters
5	1.5	900	3407	1800	6813	3300	12490
10	3.0	660	2498	1320	4996	2820	10670
15	4.6	360	1363	720	2725	2220	8400
20	6.1	---	---	---	---	1500	5680
30	9.1	---	---	---	---	300	1140
Shut-off Head		19 ft. (5.8 m)		20 ft. (6.1 m)		33 ft. (10.1 m)	

*Model LM44 not to be used as a sump pump.

MODEL 42 - 44 - 46

FLOOR SUCKER SERIES

UTILITY PUMPS



**1/6 HP
Model 42**



**1/4 HP
Model 44**



Certified to CSA
Standard C22.2 No.108



**1/4 HP
Model LM44
Automatic**



**1/2 HP
Model 46**



SSPMA
Certified
20 YEARS

USE FLOOR SUCKER SUBMERGED OR ON ANY FLAT SURFACE TO PUMP CLEAR WATER.