

AquaVantage® AV TAG

Z6000AV-2

AquaVantage® 'AV' Exposed Water Closet Flush Valve





Flow Options

-ONE*	1.1 gpf High Efficiency Flush
-HET*	1.28 gpf High Efficiency Flush
-WS1	1.6 gpf Low Consumption Flush
-WS	3.5 gpf

Accessories


□-BG	BioCare Handle
□ -DF	Dual Flush Handle
□ -H	Handle on Front of Flush Valve
□ -HL	1" [25] Metal Push Button on Front
□ -HL3	3" [76] Metal Push Button on Front
□-YH	One Wall Bumper
□-YJ	Split Ring Pipe Support
□-YK	Solid Ring Pipe Support
□-YL	Solid Ring Pipe Support with Bumper
□ <i>-</i>	Other



*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

ZURN INDUSTRIES, LLC. ◆ COMMERCIAL BRASS OPERATION
5900 ELWIN BUCHANAN DRIVE ◆ SANFORD NC 27330
PHONE: 1-800-997-3876 ◆ FAX: 919-775-3541
WWWZURN.COM
IN CANADA: ZURN INDUSTRIES LIMITED
7900 GOREWAY DRIVE UNIT 10 ◆ BRAMPTON, ONTARIO L6T5W6

PHONE: 905-405-8272 FAX: 905-405-1292



ENGINEERING SPECIFICATIONS

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior.

- Zurn's AquaVantage® TPE diaphragm Clog Resistant Triple filtered by-pass Chloramine resistant Dual seal
- Proprietary DR resistant low lead brass alloy
- Handle

ADA compliant

Non-hold open and no leak feature

Control Stop

Internal siphon-guard protection

Vandal resistant stop cap

Sweat solder kit

Cast wall flange with set screw

Vacuum Breaker

High back pressure

One piece hex coupling nut

Internal seals

Chloramine resistant

- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.