



Z6933

AquaSense Battery-Powered Faucet

TAG _____

Architectural/Engineering Specification:

Designed for modern commercial restrooms, the AquaSense Z6933 sensor faucet delivers a superior user experience in both form and function. This faucet maintains a sleek and simple design that is easy to install and user-friendly. easy to install and user-friendly handwashing solution.

This faucet has been designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

Product Features:

- Infrared convergence-type proximity sensor
- 60 second time out feature
- In-line filter
- 4 "AA" batteries
- 45" sensor cable
- 24" hose

Suffix Options:

- MV Temperature Mixing Valve
- TMV-1 Thermostatic Mixing Valve for Single Faucets
- SH Supply Hoses for Mixing Valve
- SSH Single Supply Hose
- CP4 4" Cover Plate

Compliance and Certification:

- ADA Compliant
- ASME A112.18.1/CSA B125.1
- Lead Free Compliant
- Texas Accessibility Standard (TAS)



*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



Aerator Options:

	Flowrate GPM [LpM]	WaterSense* Labeled	Outlet Type
Standard	0.5[1.9]		Spray
-L	1.0[3.8]	✓	Spray

Architectural/Engineering Approval

Rough-in dimensions/Overview dimensions

