Rev. A	Date: 5/22/09	C.N. No. 108840
Dwg. No	. 93125	Product No. Z867B0-XL

## **OPTIONAL ACCESSORIES**

4[102]

8[203]

Note: All dimensions are for reference only. Do not use for pre-plumbing

Suffix	Description
CWO	Cold Water Only
G	1-1/4" [32mm] Grid Strainer Drain
GH	1-1/4" [32mm] Offset Handicap Drain
ICT	Inter-connecting Copper Supply Tubes for 8" In-line Centers
IN	Institutional Handle - Tamper-Proof and Vandal-Resistant
P	1-1/4" [32mm] Pop-up Drain
PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
RKR	ADA Compliant Rocker Handle
140	140° Restricted Swing Spout
3F	0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
16F	1.0 GPM [3.8L] Vandal-Resistant Pressure Compensating Female Spray Outlet
ZURN IND	DUSTRIES, LLC ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733 Phone: 1-716-665-1132 ♦ Fax: 1-716-665-1135 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED + 3544 Nashua Drive + Mississauga, Ontario L4V1L2 + Phone: 905/405-8272 Fax: 905/405-1292

Zurn Lead Free products (-XL), is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn Lead Free products (-XL) are manufactured with less than one quarter of one percent (0.25%) total lead content by weighted average.

<sup>1</sup>/<sub>8</sub>[3] TO 1<sup>1</sup>/<sub>8</sub>[29] WARE

 $4\frac{1}{4}[108]$ 

14 NPSM

COUPLING NUT

11[279]

 $6\frac{7}{8}[175]$ 

Engineering Specifications: Zurn AquaSpec<sup>®</sup> Z867B0-XL

Polished chrome-plated 8" [203mm] widespread faucet with a 5-3/8" [137mm] centerline rigid or swing gooseneck spout, slow-closing metering cartridges, and vandal-resistant ADA compliant color-coded metal handles. Easily adjustable cycle time, preset to 10 seconds at 80 PSI. Unit is furnished with a water-conserving aerator which reduces flow to .25 GPC [.95 L] (complying with ANSI A112.18.1 Standard for flow), mounting hardware, 1/2" NPSM coupling nuts for standard lavatory risers and integral shank filters.

Ø2[51]



 $\phi 1 \frac{1}{8} [29]$ 

MIN. WARE

 $\phi 1\frac{1}{4}[32]$ 

ZURN

FREE



TAG

5<u>8</u>

[137]

ADA DESIGNED