

Product Name:	ABT-49S
Description:	<p>Premier Solid Door Laboratory Refrigerator  49 Cu. Ft. capacity  Two swing solid doors, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Casters with footed brake  probe access port (3/8")  White powder-coated steel exterior and interior  CFC-free refrigerant (R134a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three  compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 54"W x 34 ¾"D x 79 ¾"H  Cycle defrost  115V, 60 Hz, 7 Amps, 1/2 HP  UL/C-UL listed  Shipping weight: 528 lbs.</p>