

Product Name:	ABT-72S
Description:	<p>Premier Solid Door Laboratory Refrigerator 72 Cu. Ft. capacity Three swing solid doors, self-closing, right hinged, not reversible Microprocessor Temperature Controller Adjustable operating temperature range: 1°-10°C Standard Digital Temperature Display and Alarm Module Sample simulated digital temperature display; .1° Resolution Adjustable temperature display in Celsius or Fahrenheit Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Resettable 1-point Min/Max History Remote alarm contacts Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Twelve adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle LED interior lights are safety shielded and switch controlled Casters with footed brake probe access port (3/8") White powder-coated steel exterior and interior CFC-free refrigerant (R134a), foam insulation and packaging Two year parts and labor warranty, plus an additional three compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 81"W x 34"D x 79 ¾"H Cycle defrost 115V, 60 Hz, 10 Amps, 3/4 HP UL/C-UL listed Shipping weight: 723 lbs.</p>