Product Name:	ABT-HCPP-49G-TS
Description:	TempLog Premier Pharma Laboratory Refrigerator
	49 Cu. Ft. Capacity Two swing glass doors, self-closing (energy efficient, double pane vacuum insulated)
	Multi-Point temperature mapping via NIST traceable data acquisition, 15 probes in air and 3 probes
	, , , , , , , , , , , , , , , , , , , ,
	in sample solution for 360 minutes with temperature readings every 60 seconds
	Touch Screen Temperature Display & Alarm Module:
	Microprocessor temperature controller
	Adjustable operating temperature range: 1°C - 10°C
	Touch Screen Digital Temperature Display and Alarm Module
	Password-protected control panel
	Sample simulated digital temperature display; .1° Resolution, adjustable temperature
	display in Celsius or Fahrenheit
	Active temperature scale bar display
	Resettable 1-point min/max history Digital 24-hour temperature chart
	Temperature & alarm event data logging
	USB port for data transfer and software updates
	Real-time operational display clock
	4-20mA output
	Electronic troubleshooting guide
	Electronic Rodbleshooting guide Electronic QR Code to access Owner's Manual & technical support contact Information
	Adjustable alarm volume
	Audible and visual high/low temperature alarms
	Sensor error alarm
	Power failure alarm
	Door ajar alarm
	Low battery alarm
	Operation indicator
	Alarm validation (audible, visual, and remote alarm)
	Alarm mute with ring back
	Remote alarm contacts
	Six shelves (adjustable in ½" increments)
	Keyed door lock
	Magnetic door gasket for positive seal
	Heavy duty door handles
	Swivel casters adds 5" to height
	Interior light
	Probe access port (3/8")
	Stainless steel interior/exterior
	High density urethane foam cabinet insulation
	HFC-free refrigerant (R290a), foam insulation and packaging
	Quality certified with 100% unit temperature testing
	Three year parts and labor warranty, plus an additional two year compressor parts warranty
	Exterior dimensions: 54 1/8 "W x 31 5/8 "D x 83 5/16" H with casters;
	78 5/16 "H without casters
	Cycle defrost
	115V, 60 Hz, 5.8 Amps, 1/3 HP
	UL/C-UL listed
	Shipping weight: 530 lbs.