

# AREZZO Insert



LED lamps



hidden metallic in/out knob controls



professional stainless steel baffle filters

Arezzo provides professional grade performance, while being discreetly mounted inside the cabinetry.

Arezzo is available in 28 1/2" width with a 600 CFM blower, and equipped with a 1200 CFM blower for widths of 34 1/2", 40 1/2" and 46 1/2" for extraordinary ventilating power.

The extra depth (22") is ideal for supporting powerful professional ranges. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED lighting.

Easy maintenance, higher efficiency and a cleaner kitchen are ensured by Elica's Professional Baffle Filters, which capture a higher percentage of contaminants and hold larger volumes of grease than traditional baffle filters. Arezzo is designed for standard ducted installation only.

## ELICA PRO SERIES

## **Dimensions** | Models

28 1/2" W x 22" D x 11 1/2" H | EAR628S3 Arezzo 28" Stainless

34 1/2" W x 22" D x 11 1/2" H | EAR134S3 Arezzo 34" Stainless

40 1/2" W x 22" D x 11 1/2" H | EAR140S3 Arezzo 40" Stainless

46 1/2" W x 22" D x 11 1/2" H | EAR146S3 Arezzo 46" Stainless






PLUS

Size (in) & Type	28″, 34″, 40″ or 46″ Wide Insert
Finish	Stainless steel
Controls	IN/OUT Backlit Knob
Illumination	2 LED (28" & 34") 7.5 watts LED light, repleaceable lamps (1 intensity) 4 LED (40" & 46") 7.5 watts LED light, repleaceable lamps (1 intensity)
Installation Type	Ducted Installation Only
Blower Type	600 CFM, 4-Speed Internal (28" Unit) 1200 CFM, 4-Speed Internal (34", 40", 46" Units)
Blower Performance	Speed 1 (For 28") 90 CFM, (For 34", 40" & 46") 380 CFM Speed 2 (For 28") 330 CFM, (For 34", 40" & 46") 660 CFM Speed 3 (For 28") 490 CFM, (For 34", 40" & 46") 950 CFM Speed 4 (For 28") 600 CFM, (For 34", 40" & 46") 1200 CFM
Noise (sones):	28" Unit: Min: 2.05, Max: 7.05 Sones 34", 40", 46" Units: Min: 2.05, Max: 7.05 Sones
Filter Type	Dishwasher-Safe, Professional Stainless Steel, Angled Baffle Filters 2 (28", 34", 40" Units ) 3 (48" Unit)
Duct Transition	10" Round with Back Draft Damper (top only)
Electrical	120V-60Hz
Warranty	2 Year Parts & Labor, In-Home Service

## Line Drawing



		Models			
	EAR628S3	EAR134S3	EAR140S3	EAR146S3	
A	28 ½" (72.4 cm)	34 ½" (87.6 cm)	40 ½" (103 cm)	46 ½" (118 cm)	
В	22″ (55.9 cm)				
C 57/16″ (13.8 cm)					
D	D 6½" (16.4 cm)				
Е	27 %6″ (70 cm)				
F	F 12‰" (31.6 cm)				
G	5 29 <sup>1</sup> ¾6″ (75.7 cm)				
н	10½" (25.7 cm)				
I	10″ (25.4 cm)				
J	<sup>3</sup> ⁄4″ (1.9 cm)				

#### Accessories

### Replacement Grease Filter (1) CODE: GF061A

Consumable parts are sold in units of one (1). Order accordingly.



### HUSH S Y STEM

An exclusive sound deadening technology that effectively reduces sound levels by over 35%, compa red to typical range hood s.



#### inpa red to

LED LIGHT LED lighting is undoub tedly the sma rtest solution in terms of energy saving. Expe cted life 20.000 hour s, represents the most rema rkable ad vantage of LED lig ht bulb s.

#### P R OFESSIONAL PERFOR MANCE

Special features and very high performances for models with aspiration capacity between 200 CFM's, and noise level between 65 and 75 db (A) at maximum speed. The ideal comple range s.

#### HE AT G UARD



A safety feature that protects the hood and cabinet ry from excessive heat, by sensit tempe ratures (>158 degrees) and will automatically adjusts the blower speed to HIGH. Bl will au tomatically adjust back on ce tempe ratures d rop to a sa fe le vel.

