

	CONVENTIONAL		MODULAR		
	5 BURNERS		4 BURNERS	2 BURNERS	
	FA-950SLTX	FA-850SLTX	FA-640STX	FA-320SX	
<b>GENERAL SPECIFICATIONS</b>					
Number of burners	5	5	4	2	
Triple Crown Burner	■	■	■		
Universal ignition	■	■	■	■	
Cast iron enameled grates	3	3	2	1	
Metallic knobs	■	■	■	■	
Power supply cable with plug ( length 59 inches)	■	■	■	■	
<b>OPERATING CONTROL</b>					
Gas burners	5	5	4	2	
Control location	front	front	front	front	
<b>SAFETY</b>					
Covered Electronic ignition	■	■	■	■	
Thermocouple safety system	■	■	■	■	
Sealed burners	■	■	■	■	
<b>TECHNICAL SPECIFICATIONS</b>					
Gas burners	Auxiliary burner (5,000 BTU/h)	front left	front left	front right	front
	Semi-Rapid burner (6,800 BTU/h)	back right back left	back right back left	back right back left	
	Rapid burner (8,500 BTU/h)	front right	front right		rear
	Triple crown burner (16,000 BTU/h)	Independent	Independent	front left	
Power (V/Hz/Amp)	110/60/5.45	110/60/5.45	110/60/5.45	110/60/5.45	
<b>ACCESSORIES (units adjusted for Nat. gas from factory)</b>					
Terminal with gasket for LPG	■	■	■	■	
Fixing set	■	■	■	■	
Conversions kit for LPG	■	■	■	■	
<b>DIMENSIONS</b>					
Dimensions (inches)	Width	33.86"	30.31"	22.83"	11.81"
	Depth	20.07"	20.07"	20.07"	20.07"
	Height	2.15"	2.15"	2.15"	2.15"

**IMPORTANT**  
Ventilation instructions  
for installing Fagor  
conventional cooktops.

