

SPECIFICATIONS	LEX730RSBI	LEX605RSBI	LEX485RSIB-2	LEX485-2
LIFT EASE™ roll top lid	S	S	S	S
ACCU-PROBE™ tempczerature gauge	S	S	S	S
JETFIRE™ ignition	S	S	S	S
Rear burner igniter	S	S	S	-
Infrared ceramic bottom burner	S	S	-	-
Stainless steel bottom burners	4	3	3	3
Ceramic infrared rear rotisserie burner	S	S	S	-
Range side burner	S	S	-	-
Infrared SIZZLE ZONE™ side burner	-	-	S	-
Stainless steel WAVE™ cooking grids	S	S	S	S
Integrated ice/marinade bucket and cutting board	S	S	S	-
i-GLOW™ backlit control knobs	S	S	S	S
Spider guard venturi and brass valves	S	S	S	S
Removable drip pan	S	S	S	S
Warming rack	S	S	S	S
Condiment trays and tool hooks	S	S	S	S
President's Limited Lifetime Warranty	S	S	S	S
ACCESSORIES	LEX730RSBI	LEX605RSBI	LEX485RSIB-2	LEX485-2
Rotisserie kit with motor	O	O	O	O
Charcoal tray	O	O	O	O
Smoker pipe	O	O	O	O
Heavy duty cover	O	O	O	O
GRILL INPUTS (BTU's)	LEX730RSBI	LEX605RSBI	LEX485RSIB-2	LEX485-2
Infrared bottom burner	16,000	16,000	-	-
Main tube burners	64,000	48,000	48,000	48,000
Side burner	11,000	11,000	12,500	-
Rear infrared burner	15,000	15,500	13,500	-
Total	106,000	90,500	74,000	48,000
DIMENSIONS	LEX605RSBI	LEX605RSBI	LEX485RSIB-2	LEX485-2
Total width in inches (cm)	75 ¼ (191)	68 ½ (174)	61 ¾ (157)	61 ¾ (157)
Total depth in inches (cm)	27 ¾ (69)	27 ¾ (69)	27 ¾ (69)	27 ¾ (69)
Total height in inches (cm) lid open/lid closed	59 ¾ (151) /49 ¾ (125)	59 ¾ (151) /49 ¾ (125)	59 ¾ (151) /49 ¾ (125)	59 ¾ (151) /49 ¾ (125)

S = standard O = optional