accuc@ld

VT65MLBIMEDDTADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in freezer capable of -25° C operation; includes digital thermostat, audible alarm, lock, and hospital grade plug

Highlights:

32" height fits under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 24" wide spaces

Factory installed lock provides security you can count on

Product Features:

ADA compliant	32" high to fit under lower ADA compliant counters	
Built-in capable	Make the best use of space by installing your appliance under the counter	
-25°C capable	Low temperature capability ideal for certain sensitive items	
Manual defrost	Efficient performance with reliable temperature stability	
Factory installed lock	Keyed lock for secure interior	
Digital thermostat	Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience	
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Pull-out drawers	Clear baskets for convenient and separated storage	





accuc@ld

VT65MLBIMEDDTADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.13" (115 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	104.0 lbs. (47 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Shelf Type	Glass
Thermostat Type	Digital
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Compressor Step Depth Temperature Range	5.5" (14 cm) -20°C to -30°C



