



**Additional Dimensions: (Part # 3333 & 3332)**

- Exterior Projection is 3<sup>1</sup>/<sub>16</sub>"
- Interior Projection Depends on Handle Style
- Overall Grip thickness: 2<sup>1</sup>/<sub>8</sub>"
- Clearance between door & grip is 1<sup>9</sup>/<sub>16</sub>"
- Plates thickness: 1/2"

**Same dimensions for dummy function**

**\* Available in Lever/ Knob by Knob Mortise Entrance Handlesets. Same dimensions as interior trim of standard mortise entrance handlesets.**

Door Thickness Specifications		
<p><b>Standard Door Thickness: 1<sup>3</sup>/<sub>4</sub>"</b></p> <p>Standard Components:</p> <ul style="list-style-type: none"> <li>• 1 1/2" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2" Top Rosette Screw</li> <li>• 1 1/2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul>	<p><b>Extended Door Thickness: 1 7/8"- 2 1/4"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1 1/2" Threaded Cylinder</li> <li>• 2" Long Spindle</li> <li>• 2 1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Thumbpress</li> <li>• Strikeplate</li> </ul>	<p><b>Extended Door Thickness: 2 3/8"- 2 5/8"</b></p> <p>Extended Components:</p> <ul style="list-style-type: none"> <li>• 1 3/4" Threaded Cylinder</li> <li>• 2 1/4" Long Spindle</li> <li>• 2 1/2" Top Rosette Screw</li> <li>• 2" Bottom Rosette Screw</li> <li>• Extended Thumbpress</li> <li>• Extended Strikeplate</li> <li>• <b>2 3/4" TD Requires 2" Threaded Cylinder</b></li> </ul>