

	Product Specifications for ES93104			
ı	Job Name:	Job Type:		
		21		
	Quantity:	Comments		

	: [[
1	

ES93104 Carte 4-light Pendant Frame

Finish Glass/Shade Product Category
Satin Nickel Pendant System

Lamping		Measurements		Shipping
Number of Bulb(s)	4	Width	4.00"	Carton We
Light Type	Fluorescent	Height	3.00"	Carton Wid
Bulb Type	G24q-1 Quad T4 CFL	Length	33.00"	Carton Hei
Max Bulb Wattage	13	Extension	N/A	Carton Ler
Max Fixture Wattage	52	Back Plate Width	N/A	Carton Cu
Rated Life	±10,000 Hours	Back Plate Height	N/A	Master Pag
Rated Lumens	±3,120	HCO	N/A	Master Pag
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pag
Bulb(s) Included	No	Max Overall Height	60.00"	Master Pag
Light Up/Down	N/A	Hanging Weight	6.31 lb(s)	Master Pag
Beam Spread	N/A	Height Adjustable	Yes	Master Cu
CRI	N/A	Slope	120°	UPS Shipp
Photo Cell Included	N/A	Chain Length	N/A	
Ballast/Driver/Transformer	Yes	Wire Length	120.00"	
Dimmable	No	Canopy Width	N/A	
		Canopy Height	N/A	
		Canopy Length	N/A	

	Shipping	
1	Carton Weight	8.00 lb(s)
	Carton Width	6.50"
,	Carton Height	5.25"
	Carton Length	26.00"
	Carton Cubic Feet	N/A
	Master Pack	1
	Master Pack Weight	N/A
	Master Pack Width	N/A
	Master Pack Height	N/A
	Master Pack Length	N/A
	Master Cubic Feet	N/A
	UPS Shippable	Yes

284 N/A

Certification		Other		Equivalents
Safety Rating	Dry	UPC Code	845094018346	Incandescent Watts
Energy Star	No	Material	N/A	Fluorescent Watts
CA Title 24	No			
CA Title 20	No			
ADA	No			

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.