

TECHNICAL SPECIFICATIONS



Luna™ Whirlpool Bath

LUN7242 WCR 2XX Luna Whirlpool Bath Right Hand (BF75)

LUN7242 WCL 2XX Luna Whirlpool Bath Left Hand (EK75)

Luna™ Bath

LUN7242 BCX XXX Luna Bath (ES75)

INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

KEY DIMENSIONS

DIMENSIONS

72" L x 42" W x 23" H

(1829 mm) L x (1067 mm) W x (584 mm) H

DRAIN/OVERFLOW

A: 19-1/8" (486 mm) B: 11" (279 mm)

CUTOUT

Template Provided: P/N P819000

TOTAL WEIGHT

BF75, EK75: 1221 lb (554 kg) / 58 lb/ft² (283 kg/m²)

ES75: 1219 lb (554 kg) / 64 lb/ft² (313 kg/m²)

OPERATING GALLONAGE

BF75, EK75: Min. 82 U.S. Gal. (310 Liters)

Max. 103 U.S. Gal. (390 Liters)

PRODUCT WEIGHT

BF75, EK75: 115 lb (52 kg)

ES75: 64 lb (29 kg)

SKIRT MOUNTING

Not Available

ELECTRICAL SPECIFICATIONS MODELS BF75, EK75 ONLY

Requires a dedicated GFCI protected separate unit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz.

RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

HEATER (OPTIONAL) MODELS BF75, EK75 ONLY

Requires a dedicated GFCI protected separate unit.

RapidHeat™: P/N S750000

Heater Blank: P/N BZ96000

Product Shown: Luna Whirlpool Bath Right Hand

Shown Model: BF75

Minimum Service Access dimensions given.

* Measurements inside unit represent cutout in floor to allow for drain/overflow.

FEATURES, UPGRADES & ACCESSORIES

- Left and Right Hand Drain Location
- Accessories / Hardware:
 - Trip-Lever Drain Kit: #X559
 - Rotary Drain Kit, 26" Cable: #8730
 - TheraPro™ Jet Rings Kit: #GU44
 - AccuPro™ Jet Rings Kit: #GU45
- Trim Kit Finishes Available:
 - (827) – Chrome
 - (826) – Brushed Nickel
 - (845) – Oil Rubbed Bronze

