

CATHEDRAL™



15429 TZT

PIERCED
DOME



AZT

15457 AZT

Ordering Guide & Finish	15429 TZT	15457AZT
Housing	Aluminum	Cast Aluminum
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)
LED Lamp Options	2W (18039-18041) see page 137. Compares up to 16W Xenon.	2W (18039-18041) see page 137. Compares up to 16W Xenon.
Wiring	24" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	24" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket
Integrated LED Options	N/A	15857 on page 48
Photometric with Supplied Lamp	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'
	Foot Candles	7.52 5.42 0.47 1.15 0.32 0.05 – – –
	Distance from Light	0' 1' 2' 3' 4' 5' 6' 7' 8'
	Foot Candles	9.36 5.22 3.76 2.02 0.89 0.12 0.05 – –