

12V LED ACCENT

12V LED ACCENT



	15731, 15732, 15733 AZT, BBR, BKT	15741, 15742, 15743 AZT, BBR, BKT	15751, 15752, 15753 AZT, BBR, BKT
Ordering Guide & Finish	15731 AZT, BBR, BKT – 10° Spot 15732 AZT, BBR, BKT – 35° Flood 15733 AZT, BBR, BKT – 60° Wide Flood	15741 AZT, BBR, BKT – 10° Spot 15742 AZT, BBR, BKT – 35° Flood 15743 AZT, BBR, BKT – 60° Wide Flood	15751 AZT, BBR, BKT – 10° Spot 15752 AZT, BBR, BKT – 35° Flood 15753 AZT, BBR, BKT – 60° Wide Flood
Housing	Cast Aluminum or Cast Brass with clear tempered glass lens and polycarbonate mounting stem and locknut		
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	6 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	9 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI		
Optics	Custom T.I.R. (Total Internal Reflection) Acrylic Optics		
Power Usage	4.5 W, 7.5 VA	8.5 W, 12.2 VA	12.4 W, 16.7 VA
Watts/Lumens	Comparable to 20 W MR16	Comparable to 35 W MR16	Comparable to 50 W MR16
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		
Lumen Maint.	Tested to an L-70 of 40,000 hours		
Delivered Lumens & Efficacy	3000K = 150 Lm 3000K = 33 Lm/W	3000K = 310 Lm 3000K = 36 Lm/W	3000K = 460 Lm 3000K = 37 Lm/W
Wiring	53" of usable #18-2, SPT-1-W leads. Cable connectors supplied.		
Mounting Access. (Included)	8" slotted in-ground stake		
Optional Accessories	15601 – Surface Mounting Flange 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15607 – Surface Mounting Bracket 15645, 15656, 15657, 15658 or 15570 – Stems		
Optional Cowl Accessories	15701 AZTP, BKTP Short Cowl for use with 4.5W and 8.5W size 15702 AZTP, BKTP Short Cowl for use with 12.4W size 15703 AZTP, BKTP Long Cowl for use with 4.5W and 8.5W size 15704 AZTP, BKTP Long Cowl for use with 12.4W size For BBR fixture finishes, use AZTP		
Optional Lens Accessories	Amber – Offers warmer hues of light 15875 AMB For use with 4.5W/8.5W size 15876 AMB For use with 12.4W size	Green – Intensify the greens of foliage 15885 GRN For use with 4.5W/8.5W size 15886 GRN For use with 12.4W size	Frosted – Diffuse light where you need it 15895 FRO For use with 4.5W/8.5W size 15896 FRO For use with 12.4W size