

### Product Information

Applicable products:	
BubbleMassage bath – less chromatherapy	K-1110-G
BubbleMassage bath – with chromatherapy	K-1110-GCR

Fixture*:	
Bathing well:	
Basin area, bottom	45" (114.3 cm) x 25-1/2" (64.8 cm)
Basin area, top	63" (160 cm) x 31-1/2" (80 cm)
Weight	134 lbs (60.8 kg)
To overflow:	
Water depth	21" (53.3 cm)
Capacity	115 gal (435.3 L)
* Approximate measurements for comparison only.	

Included components:	
Cut-out template (drop-in only)	1016369-7

Blower motor / control:	kW	V	Hz	A
	300	220-240	50/60	3

Required accessories:	
Undermount template kit (for undermount installations only)	K-589
Clearflo horizontal overflow bath drain	K-7273

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Blower motor/control	220-240 V, 15 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 49 lbs/square foot (237.5 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

This bath is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

A blower motor/control access panel is required.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain shown. (K-7273)

