

# KOHLER® Roughing-In

## K-1151-HL, K-1151-HR BANCROFT® 5' BATH WHIRLPOOL WITH HEATER

### Product Information

Applicable product:	
Bath whirlpool with heater – left drain	K-1151-HL
Bath whirlpool with heater – right drain	K-1151-HR

Fixture*:	
Bathing well:	
Basin area, bottom	45" (114.3 cm) x 22" (55.9 cm)
Basin area, top	54" (137.2 cm) x 25" (63.5 cm)
Weight	140 lbs (63.5 kg)
To overflow:	
Water depth	15" (38.1 cm)
Capacity	60 gal (227.1 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A	
1-speed	120	60	7	
Heater:	kW	V	Hz	A
	1.5	120	60 Hz	12.5

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump and heater.	

### Installation Notes

Install this product according to the installation guide.  
Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (244 kg/square meter) loading.  
Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677)

