

Product Information

Fixture:*		
Bathing well:		
Basin area, bottom	45" (114.3 cm) x 25-1/2" (64.8 cm)	
Basin area, top	63" (160 cm) x 31-1/2" (80 cm)	
Weight	160 lbs (72.6 kg)	
To overflow:		
Water depth to rim	19-1/4" (48.9 cm)	
Capacity	96 gal (363.4 L)	
* Approximate measurements for comparison only.		

	Included co	omponents:			
	Cut-out template		1016369-7		
ĺ	_		l		

Pump	Heater	V	Hz	Α
	1.5 kW	240	50/60	15

Required accessories:	
Clearflo horizontal overflow bath drain	K-7273

Required Electrical Service

Dedicated circuit required, pr Ground-Fault Circuit-Interrup Current Device (RCD):	
Pump/control	220-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Pump/piping protrudes beyond rim (see below).

Floor support under whirlpool must provide a minimum of 43 lbs/square foot (210 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements with drain illustrated. (K-7273)



