

Roughing-In 6' EXPERIENCE BATH WHIRLPOOL WITH SPA/MASSAGE PACKAGE

Product Information

Applicable product:	
6' Experience bath whirlpool with Spa/Massage Package	K-1418-V

Fixture*:	
Basin area:	
Bathing area, bottom	42" (106.7 cm) x 27" (68.6 cm)
Bathing area, top	60" (152.4 cm) x 30" (76.2 cm)
Weight	140 lbs (64 kg)
To overflow:	
Water depth	16" (40.6 cm)
Capacity	86 gal (326 L)
* Approximate measurements for comparison only.	

Pump:	kW	V	A*
	1.5	240	15
* Approximate measurements for comparison only.			

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)	
Drop-in cut-out	70-1/2" (179.1 cm) x 40-1/2" (102.9 cm)

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs/square foot (214 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

This whirlpool is designed for drop-in installation only. It is not suited for use in a three wall alcove with an overhead shower.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

