

Product Information

Applicable product:	
Bath/shower whirlpool – left drain	K-1683
Bath/shower whirlpool – right drain	K-1684

Fixture*:	
Basin area:	
Bathing well	46" (116.8 cm) x 23" (58.4 cm)
Top area	54" (137.2 cm) x 27" (68.6 cm)
Weight	200 lbs (90.7 kg)
To overflow:	
Water depth	11-7/8" (30.2 cm)
Capacity	55 gal (208.2 L)
* Approximate measurements for comparison only.	

Pump	V	Hz	A
1-speed:	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 48 lbs/square foot (232 kg/square meter) loading.

Shimming is required to level the fixture.

Stud opening tolerance [+ 1/4" (6 mm) - 0" (0 mm)]. When a fire rated wall is specified, dimensions are to the inside of the wall board. Some shimming between the stud frame and the fixture may be required.

The K-1657/K-1663 or K-1708/K-1647-PC steam generator/control kit are designed for use with this product. Kohler shall not be responsible for problems encountered due to the installation and use of other manufacturer's steam generators.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

