

KOHLER®

Roughing-In

K-4367
HIGHCLIFF™
BOWL

Product Information

Applicable product:	
Elongated bowl toilet	K-4367
Elongated bowl toilet with bedpan lugs	K-4367-L
Fixture:	
Configuration	Rear spud, elongated
Water per flush	1.6 gal (6 L)*
Spud size	1-1/2"
Passageway	2-1/4" (57 mm)
Water area	11-3/8" (289 mm) x 10-3/8" (264 mm)
Water depth from rim	6" (152 mm)
Seat post hole centers	5-1/2" (140 mm)
Minimum static pressure required	35 psi (241.3 kPa)
Maximum static pressure	80 psi (551.6 kPa)
Minimum flowing pressure required	25 psi (172.4 kPa)
Required supply minimum	25 gpm (94.6 lpm)
* Designed to flush with 1.6 gal (6 L) of water when installed with a 1.6 gpf (6 lpf) valve.	

Recommended accessories:	
Lustra™ open front seat	K-4670-C
Lustra open front seat with anti-microbial agent	K-4670-CA
Floor bolts (pair)	21401

Included components:	
Spud	18357
Bolt cap accessory pack	52048

Installation Notes

Install this product according to the installation guide.

Refer to manufacturer and local codes for flush valve requirements.

Will comply with the American Disabilities Act (**ADA**) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

