

# KOHLER® Roughing-In

**K-702-H2, K-702-N1  
VINTAGE®  
BATH WHIRLPOOL**

## Product Information

|   |          |
|---|----------|
| Applicable products:                    |          |
| Bath whirlpool                          | K-702-N1 |
| Bath whirlpool with neckjets and pillow | K-702-H2 |

|   |                                |
|---|--------------------------------|
| Fixture*:                                       |                                |
| Bathing well:                                   |                                |
| Basin area, bottom                              | 44" (111.8 cm) x 28" (71.1 cm) |
| Basin area, top                                 | 60" (152.4 cm) x 32" (81.3 cm) |
| Weight  | 555 lbs (251.7 kg)             |
| To overflow:                                    |                                |
| Water depth                                     | 15" (31.8 cm)                  |
| Capacity  | 82 gal (310.4 L)               |
| * Approximate measurements for comparison only. |                                |

| Product   | kW  | V   | A* |
|---|-----|-----|----|
| Neckjets  | 1.5 | 240 | 15 |
| Without neckjets                                | 1.5 | 240 | 11 |
| * Approximate measurements for comparison only. |     |     |    |

|                 |   |
|-----------------|---|
| Drop-in cut-out | 70-1/2" (179.1 cm) x 40-1/2" (102.9 cm) |
|-----------------|---|

No change in measurements if connected with drain illustrated. (K-7158 or K-7158M)

|                     |          |
|---------------------|----------|
| Included component: |          |
| Cut-out template    | 106594-7 |

## Required Electrical Service

|  |                           |
|--|---------------------------|
| Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD): |                           |
| Pump/control   | 208-240 V, 20 A, 50/60 Hz |

## Installation Notes

**NOTE:** Pump protrusion beyond rim.

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 61 lbs/square foot (294 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Fixture conforms to ASME Standard A112.19.1. All dimensions are nominal.

