

GROOVETM

Features


- Acrylic
- For alcove installations
- One-piece construction
- Removable drain cover
- Drain hole at rear
- 60" (152.4 cm) x 42" (106.7 cm) x 4-9/16" (11.6 cm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- CSA B45
- IAPMO/cUPC
- ANSI Z124.1.2

ACRYLIC SHOWER RECEPTOR K-9996
ALSO K-9333, K-9337



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- CP: Polished Chrome
- PB: Vibrant_® Polished Brass
- SH: Bright Silver
- NA: None applicable
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description Colors/Fit		nishes	
K-9996	60" (152.4 cm) receptor		□ 0	□ Other
Required	Accessories			·
K-9333	Aluminum drain cover OR			□ SH
K-9337	Teak drain cover			□ NA
Recomme	ended Accessories			•
	Drain	□ CP	□ PB	☐ Other

Product Specification

The acrylic shower receptor with removable drain cover shall be 60" (152.4 cm) in length, 42" (106.7 cm) in width, and 4-9/16" (11.6 cm) in height. Shower receptor shall be for alcove installations. Shower receptor shall be one-piece configuration with drain hole at rear. Shower receptor shall be Kohler Model K-9996-_____.

USA: 1-800-4-KOHLER Canada: 1-800-964-5590 kohler.com

GROOVE_{TM}

Technical Information

Fixture*:		
Weight	72 lbs (32.7 kg)	
Configuration	one-piece	
Drain hole	3-3/8" (8.6 cm) D.	
* Approximate measurements for comparison only.		

Installation Notes

Install this product according to the installation guide.

Shimming may be required to level the fixture.

Shimming may be required between the stud frame and the fixture.

The stud opening tolerance is +1/4" (6 mm), -0" (0 mm).

When fire rated construction is specified, dimensions are to the inside of the fire-rated wall.

