


Type _____

-30EB

P7128	<input type="checkbox"/>
P7129	<input type="checkbox"/>
P7130	<input type="checkbox"/>
P7131	<input type="checkbox"/>
P7132	<input type="checkbox"/>
P7133	<input type="checkbox"/>

Catalog No.	Finish	Lamping	Dimensions (Inches)		
	White		A	B	C
P7128	-30EB	1-F17T8	24-3/8	4-5/8	4
P7129	-30EB	2-F17T8	24-3/8	4-5/8	4
P7130	-30EB	1-F25T8	36-3/8	4-5/8	4
P7131	-30EB	2-F25T8	36-3/8	4-5/8	4
P7132	-30EB	1-F32T8	48-3/8	4-5/8	4
P7133	-30EB	2-F32T8	48-3/8	4-5/8	4



Specifications:

General

- Ribbed white acrylic diffuser
- Removable white plastic end caps permit lamp replacement and cleaning
- Can be mounted horizontally or vertically
- Complies with "Americans with Disabilities Act"
- Energy Star Certified

Electrical

- Bi-pin twist-in sockets for T8 lamps
- 120V electronic NPF two lamp ballasts (277V available on request)

Labeling

- UL-CUL listed

Housing

- 20ga White chassis complete with ends
- 24ga Cover plate
- 1/2" KO in back center, and one near each end for wiring
- Keyhole KO's on back near each end for mounting
- Housing covers a standard recessed 4" octagonal outlet box



Progress Lighting
701 Millennium Blvd.
Greenville, South Carolina
29607