

TOTO® USA, INC. has merged heated air and water to create the ultimate in bathing luxury:

## The TOTO® Guinevere® Air Bath™

The TOTO® Guinevere® Air Bath™ will provide the bather a soothing, relaxing and refreshing repose uniquely different than any other bath-time experience. The cast-acrylic Guinevere® Air Bath™ has smooth lines and a deep bathing well which is accented with solid brass grab bars and 16 individual air jets. The individualized check valve system allows the bather to use soaps, bath oils, salts and other bathing essentials without harming the performance of the air system.



ABA974 - Guinevere® 6' Air Bath™

- 71/1/2" x 38" x 24-3/8"
- Luxuriously deep Bathing Well
- Cast-acrylic construction provides years of durability
- Slip-resistant surface
- 1 hp Ultra-quiet Blower
- 300 watt Heated Air Injection System
- Final purge/drying cycle to clean each air jet
- Solid Brass Grab Bar with optional finishes
  
- Multi functional Keypad
  - Normal Mode -**  
5 Intensity Levels For Continuous Operation
  - Pulsating Mode -**  
Alternating between the High/Low Intensity levels for Massage
  - Oscillation Mode -**  
Alternating between all 5 Intensity levels for Massage

### ■ ABA974R

Acrylic bathtub. Slip-resistant surface. Right keypad/ left blower

### ■ ABA974L

Acrylic bathtub. Slip-resistant surface. Left keypad/ right blower

#### Colors:

Standard #01 Cotton  
#12 Sedona Beige

Grab Bar CP: Polished Chrome  
BN: Brushed Nickel  
PB: Polished Brass

Jet Trim Chrome with color matched air jets

# ABA974R/L

## Guinevere® 6' Air Bath™

### ■ STYLE

The Guinevere® Air Bath™ is designed to match all of the fixtures in the Guinevere® luxury bath suite. Cast acrylic construction provides the ultimate in strength and durability, while a slip-resistant surface enhances safety in the bath.

### ■ SPECIFICATIONS

Size: 71-1/2" L x 38" W  
 Depth: 20"

Warranty: 1 Year Limited Warranty on Acrylic Tub  
 1 Year Limited Warranty on Components and Parts

Material: Cast Acrylic

Electrical Requirements:  
 15 AMP; 120V w/GFI

Shipping Weight:  
**ABA974R/L**  
 140 lbs.

Shipping Dimensions:  
**ABA974R/L**  
 73" L x 43" W x 26" H


Gallons: **ABA974R/L**  
 98 gal. to overflow  
 50 min. operational capacity



Fixture meets ANSI/ASME standard Z124.1, ETL, and C-USPC requirements.

*These dimensions and specifications are subject to change without notice.*

*Use TOTO® cut template to assure rough in dimensions.*



ABA974L - Guinevere® 6' Air Bath™



TOTO® U.S.A., INC. • 1155 Southern Road, Morrow, GA 30260  
 Tel. (888) 295-8134 • Fax. (800) 699-4889 • www.totousa.com

Printed in U.S.A. © TOTO® LTD. 04/06 #D50290

Printed on recycled paper

REV 03/09