Product Name:	PH-ABT-S26G
Description:	26 Cu. Ft. Capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 36°F – 46°F (2°C – 8°C) Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable Four adjustable shelves (adjustable in ½" increments) Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Casters with footed brake LED interior lights are safety shielded and switch controlled Probe access port (3/8") Powder coated steel white interior and exterior High density urethane foam cabinet insulation CFC-free refrigerant (R134a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 28 3/8"W x 36 ½"D x 79 ¾"H Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP UL/C-UL listed
	Heavy duty door handle Casters with footed brake LED interior lights are safety shielded and switch controlled Probe access port (3/8") Powder coated steel white interior and exterior High density urethane foam cabinet insulation CFC-free refrigerant (R134a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs One year parts and labor warranty, plus an additional four year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 28 3/8"W x 36 ½"D x 79 ¾"H Cycle defrost 115V, 60 Hz, 6 Amps, 3/8 HP