



BRICK LIGHT




15773 AZT




15774 AZT

MINI STEP LIGHT



15782 CO



15780 AZT



AZT



BBR



BKT



WHT

15773/15774 AZT

15780/15782 AZT, BBR, BKT, CO, WHT

Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White												
Ordering Guide & Finish	15773 AZT27R 15774 AZT27R	15773 AZT30R 15774 AZT30R	15780 AZT27R 15782 AZT27R 15780 BBR27R 15782 BBR27R 15780 BKT27R 15782 BKT27R 15780 CO27R 15782 CO27R 15780 WHT27R 15782 WHT27R	15780 AZT30R 15782 AZT30R 15780 BBR30R 15782 BBR30R 15780 BKT30R 15782 BKT30R 15780 CO30R 15782 CO30R 15780 WHT30R 15782 WHT30R												
Housing	Cast Aluminum		Aluminum, Brass or Copper with white reflector. Zinc plated steel housing.													
Light Source	2 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver		1 Integrated High Output Cree® LED, tightly binned for color uniformity, and constant current driver													
Color Temp. (CCT) & CRI	2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI		2700K (-50/+100) / 80s CRI 3000K (-45/+130) / 80s CRI													
Power Usage at 12V AC Input VA and Watts	1.72 W, 3.72 VA		.86W, 1.86 VA													
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology		9V-15V AC/DC with no loss in output due to constant current technology													
Lumen Maint.	Tested to an L-70 of 40,000 hours		Tested to an L-70 of 40,000 hours													
Delivered Lumens & Efficacy	2700K = 86 Lm 2700K = 102 Lm/W	3000K = 82 Lm 3000K = 100 Lm/W	2700K = 43 Lm 2700K = 51 Lm/W	3000K = 41 Lm 3000K = 50 Lm/W												
Wiring	Wire connection must be made inside fixture		Wire connection must be made inside fixture													
Mounting Access.	Stainless steel mounting hardware and junction box (Included)		Mounting hardware and junction box (Included)													
Incandescent	15073 – on page 125, 15074 – on page 125		15072 - on page 125, 15070 - on page 125													
Notes	Designed to be integrated into brick wall during construction. LED version is also usable in vertical risers. Available with or without louvers. *Cree is a registered trademark of Cree, Inc.		Designed to be integrated into outdoor steps. Available with louvered faceplate or with acrylic lens as shown above. Copper and Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.													
Fixture Photometric (fc)*	15773 Mounting Light		15780 Mounting Light													
	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'		
	12"	0.07	0.40	1.30	0.60	0.14	0.06	0.03	6"	1.40	1.20	0.40	0.08	0.03	0.01	0.00
	24"	0.02	0.05	0.16	0.23	0.23	0.08	0.05	12"	0.09	0.40	0.29	0.13	0.04	0.02	0.01
	36"	0.01	0.01	0.83	0.08	0.11	0.13	0.08								
	15774 Mounting Light		15782 Mounting Light													
	0'	.5'	1'	2'	3'	4'	5'	0'	.5'	1'	2'	3'	4'	5'		
	12"	3.00	1.30	0.10	0.44	0.10	0.03	0.03	6"	0.92	0.38	0.56	0.00	0.00	0.00	0.00
	24"	0.06	0.20	0.30	0.20	0.10	0.08	0.04	12"	0.15	0.14	0.14	0.03	0.19	0.00	0.00
	36"	0.04	0.09	0.10	0.18	0.12	0.09	0.06								

*Values stated for 3000K. -10% for 2700K.