


## BLING II SCONCE



### Description:

The Bling II wall sconce may be mounted as an up-light or a down-light. The metal canopy and stem is available in bronze, polished chrome, and matte chrome plating. A 75W dimmable electronic transformer is included on the mounting plate.

### Part Numbers:

|                 |                            |
|-----------------|----------------------------|
| <b>100174bz</b> | bronze, amber glass        |
| <b>100174ch</b> | chrome, amber glass        |
| <b>100174mc</b> | matte chrome, amber glass  |
| <b>100179bz</b> | bronze, white glass        |
| <b>100179ch</b> | chrome, white glass        |
| <b>100179mc</b> | matte chrome, white glass  |
| <b>100843bz</b> | bronze, black glass        |
| <b>100843ch</b> | chrome, black glass        |
| <b>100843mc</b> | matte chrome, black glass  |
| <b>100844bz</b> | bronze, gold glass         |
| <b>100844ch</b> | chrome, gold glass         |
| <b>100844mc</b> | matte chrome, gold glass   |
| <b>100845bz</b> | bronze, silver glass       |
| <b>100845ch</b> | chrome, silver glass       |
| <b>100845mc</b> | matte chrome, silver glass |

### Technical Specs:

120V AC, 50/60Hz input  
11.7V AC output  
50VA, 49W for 1(maximum 50 Watt lamp)  
GY6.35 socket  
Suitable for dry locations only  
Mount to 3 1/2" - 4" round J-box  
Short circuit protection  
Overload protection  
Thermal protection  
Dimmable