

12V 6.5W LED ACCENT



16006 AZT, BBR, BKT

16007 AZT, BBR, BKT, WHT

16008 AZT, BBR, BKT

Beam Spread	Beam Spread 10° Spot		Beam Spread 35° Flood		Beam Spread 60° Wide Flood	
Kelvin	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White	2700K – Warm White	3000K – Pure White
Ordering Guide & Finish	16006 AZT27 16006 BBR27 16006 BKT27	16006 AZT30 16006 BBR30 16006 BKT30	16007 AZT27 16007 BBR27 16007 BKT27 16007 WHT27	16007 AZT30 16007 BBR30 16007 BKT30 16007 WHT30	16008 AZT27 16008 BBR27 16008 BKT27	16008 AZT30 16008 BBR30 16008 BKT30
Watts/Lumens	Compares to 35W Halogen MR16					
Housing	Cast Aluminum, Cast Brass					
Light Source	5 Integrated High Output Cree® LEDs, tightly binned for color uniformity, and constant current driver					
Color Temp. (CCT) & CRI	2700K (-50/+100) Warm White 3000K (-45/+130) Pure White / 80s CRI					
Optics	Radiax™ Reflector					
Power Usage at 12V AC Input VA and Watts	6.5W, 10.0VA					
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology					
Lumen Maint.	Tested to an L-70 of 40,000 hours					
Delivered Lumens & Efficacy	2700K = 306 Lm 2700K = 47 Lm/W		3000K = 352 Lm 3000K = 54 Lm/W			
Wiring	24" of usable #18-2, SPT-1W leads. Wire connectors supplied. Includes LVPC installed. See page 134.					
Mounting Access. (Included)	8" slotted in-ground stake					
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Bracket 15645, 15656, 15657, 15658 or 15570 – Stems		15609 – Junction Box Mounting Bracket 15647 – 90° Elbow			
Notes	Textured white only available in 35° beam. Brass will naturally patina over time. *Cree is a registered trademark of Cree, Inc.					