INSTALLATION INSTRUCTIONS

Rev. 08/23/2012

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

- 1. Shut off power at the fuse box or circuit breaker box. Remove old fixture from ceiling, including the crossbar.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. Thread the Mounting Screw about 1/4" into the pre-drilled holes in the Crossbar spaced the same distance apart as the holes in the Ceiling Pan (A).
- Attach the Crossbar to the Outlet Box using the two Screws from the outlet box. The side of the Crossbar marked "GND" must face out.
- 5. While holding the ceiling pan (A) toward the ceiling, connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture wire to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect the fixture ground wire to it. Otherwise, connect the fixture ground wire directly to the crossbar using the green screw provided. After wires are connected, tuck them carefully inside the Junction Box as you hold the Ceiling Pan assembly towards the ceiling.
- Finish mounting the Ceiling Pan assembly by placing it over the Nipple on the crossbar and secure the Ceiling Pan assembly against ceiling with Finial.
- Install the light bulbs in accordance with the fixture's specifications. (DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
- Place the Plastic Washer (C) and Cover centered with glass panel (B) over the studs located on the Ceiling Pan (A) and secure with Knurled Knobs (D) tightly.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.





