accucold

VLT184



32.5" x 65.25" x 29.25" (H x W x D)

-35°C laboratory 17.2 cu.ft. chest freezer with stainless steel corner guards, NIST calibrated thermometer with alarm, and lock

Highlights:

Designed to operate at -35°C for select laboratory, pharmacy, industrial, and other institutional storage needs

Includes an external NIST calibrated readout of the current and high/low temperature with an audible alarm

Manual defrost operation and static cooling system

Product Features:

Low temperature chest freezer	Operates at -35°C for use in laboratories, research facilities, and other settings with lower temperature cold storage needs	
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
Certificate of calibration	2-year certificate included for your records	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines	
Factory-installed lock	Added security with a locking lid (2 keys included)	
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed	
Digital controls	Externally located digital thermostat allows you to adjust the temperature as needed without opening the lid	
Counterbalanced hinges	The lid will remain open once lifted for easier loading	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



accuceld

VLT184 Specifications:

Height of Cabinet 32.5" (83 cm) Width 65.25" (166 cm) Depth 29.25" (74 cm) Depth with Handle 31.0" (79 cm) Capacity 17.2 cu.ft. (487 L) Defrost Type Manual Door White Cabinet White US Electrical Safety ETL Canadian Electrical ETL-C Saritation ETL-S Amps 3.6 Voltage/Frequency 115 V AC/60 Hz Weight 170.0 lbs. (77 kg) Shipping Weight 175.0 lbs. (79 kg) Parts & Labor Warranty 1 Year Compressor Warranty 5 Years UPC 761101086439 Freezer 2000 Interior Height 25.0" (64 cm) Interior Depth 21.5" (55 cm) Thermostat Type Digital Refrigerant Type 289 oz. High Side PSI 400.0 Low Side PSI 200.0 Wheels 6 Compressor Step Height 11.75" (3	Overview			
Depth 29.25" (74 cm) Depth with Handle 31.0" (79 cm) Capacity 17.2 cu.ft. (487 L) Defrost Type Manual Door White Cabinet White Canadian Electrical Safety ETL-C Safety ETL-C Sanitation ETL-S Amps 3.6 Voltage/Frequency 115 V AC/60 Hz Weight 170.0 lbs. (77 kg) Shipping Weight 175.0 lbs. (79 kg) Parts & Labor Warranty 1 Year Compressor Warranty 5 Years UPC 761101086439 Freezer Door Swing Interior Height 25.0" (64 cm) Interior Depth 21.5" (55 cm) Thermostat Type Digital Refrigerant Amount 2.89 oz. High Side PSI 400.0 Low Side PSI 200.0 Wheels 6 Compressor Step Weidth 11.75" (30 cm)	Height of Cabinet	32.5" (83 cm)		
Depth with Handle 31.0" (79 cm) Capacity 17.2 cu.ft. (487 L) Defrost Type Manual Door White Cabinet White Canadian Electrical Safety ETL Canadian Electrical ETL-C Safety Safety Sanitation ETL-S Amps 3.6 Voltage/Frequency 115 V AC/60 Hz Weight 170.0 lbs. (77 kg) Shipping Weight 175.0 lbs. (79 kg) Parts & Labor Warranty 1 Year Compressor Warranty 5 Years UPC 761101086439 Freezer 25.0" (64 cm) Interior Height 25.0" (64 cm) Interior Depth 21.5" (55 cm) Thermostat Type R290a Refrigerant Type R290a Refrigerant Type 289 oz. High Side PSI 400.0 Low Side PSI 200.0 Wheels 6 Compressor Step Height 11.75" (30 cm)	Width	65.25" (166 cm)		
Capacity17.2 cu.ft. (487 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty5 YearsUPC761101086439Freezer100 SwingInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Depth	29.25" (74 cm)		
Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerDoor SwingInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Depth with Handle	31.0" (79 cm)		
DoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439Freezer100 SwingInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Type200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Capacity	17.2 cu.ft. (487 L)		
CabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetyETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty5 YearsUPC761101086439Freezer100 SwingInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Defrost Type	Manual		
US Electrical SafetyETLCanadian Electrical SafetyETL-C SafetySanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerUPCDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Door	White		
Canadian Electrical SafetyETL-C SafetySanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerEndDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Cabinet	White		
SafetySanitationETL-SAmps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeRe290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	US Electrical Safety	ETL		
Amps3.6Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439Freezer1000 SwingInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeRegoaRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)		ETL-C		
Voltage/Frequency115 V AC/60 HzWeight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerUPCDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeRefrigerant TypeHigh Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Sanitation	ETL-S		
Weight170.0 lbs. (77 kg)Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerInterior HeightDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeRe290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Width11.75" (30 cm)	Amps	3.6		
Shipping Weight175.0 lbs. (79 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerItterior WeightDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Voltage/Frequency	115 V AC/60 Hz		
Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086439FreezerPartsDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height11.75" (30 cm)	Weight	170.0 lbs. (77 kg)		
Compressor Warranty5 YearsUPC761101086439FreezerDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Shipping Weight	175.0 lbs. (79 kg)		
UPC761101086439Freezer761101086439Door SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Parts & Labor Warranty	1 Year		
FreezerDoor SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height11.75" (30 cm)	Compressor Warranty	5 Years		
Door SwingLift-UpInterior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	UPC	761101086439		
Interior Height25.0" (64 cm)Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Freezer			
Interior Width59.0" (150 cm)Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Door Swing	Lift-Up		
Interior Depth21.5" (55 cm)Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Interior Height	25.0" (64 cm)		
Thermostat TypeDigitalRefrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Interior Width	59.0" (150 cm)		
Refrigerant TypeR290aRefrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Interior Depth	21.5" (55 cm)		
Refrigerant Amount2.89 oz.High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Thermostat Type	Digital		
High Side PSI400.0Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Refrigerant Type	R290a		
Low Side PSI200.0Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Refrigerant Amount	2.89 oz.		
Wheels6Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	High Side PSI	400.0		
Compressor Step Height10.25" (26 cm)Compressor Step Width11.75" (30 cm)	Low Side PSI	200.0		
Compressor Step Width 11.75" (30 cm)	Wheels	6		
	Compressor Step Height	10.25" (26 cm)		
Compressor Step Depth 21.5" (55 cm)	Compressor Step Width	11.75" (30 cm)		
		21.5" (55.cm)		



